A long history of shaking things up

Savage Shakers



The remarkable story of Savage Equipment begins with the Savage Shaker. It was the first piece of machinery developed here, and it was the first of its kind for the nut-harvesting industry. Through almost five decades of upgrading our shakers, we have perfected them into these finely crafted, rugged machines. They are now helping growers get the job done in many parts of the globe.

The Savage family of shakers includes five models—a size to accommodate virtually every tractor size and tree-trunk diameter. They are built to take the punishment of shaking and be gentle on your trees. You can see them in action on our website, or www.youtube.com/savageequipmentinc.

SAVAGE

Madill, OK: 580-795-3394 | Baconton, GA: 229-787-5115 | Mesquite, NM: 575-233-2964 www.savageequipment.com

Savage Shakers



Preparing to clamp onto a "big one" with our largest model, the 2158



Clamped and ready to shake with our smallest model, the 2138



Just a few seconds of shaking brings a shower of leaves and nuts.

No other piece of orchard equipment takes the kind of punishment a tree shaker does. That's why it's important to go with a proven industry leader. By testing our equipment season after season in our own pecan orchard, we're able to perfect Savage designs year-by-year, and produce equipment that provides real value and is built to last.

It's simple! A better shaker means a better harvest.

Savage Shaker Features:

- o Simple and quick tractor mounting
- Heavily braced, reinforced clamp arm
- Easily removed bearings and simple access to shaking components
- Oversized adjustable drive chain
- Easily changed tree pads
- Tree-friendly donut pads standard on 2138
 & 2158 (optional on other shaker models)
- Precision milled and over-engineered throughout to last many harvest seasons



Savage tree shakers feature double welding and thick steel plates in all the right places. They're engineered to shake hard and still be easy on your trees.



Model	Min. Tree	Max Tree	Shake Pwr.	Weight	PTO/HP
Number	Diameter	Diameter	Index		Required
2138	0"	30"	2.0	1320	540/45HP
2542	*12"	*42"	4.8	2050	540/70HP
2548	*4"	*48"	5.0	2210	1000/90HP
2653	*10"	*53"	6.5	2490	1000/100HP
2158	10"	58"	7.5	2850	1000/115HP

^{*} Subtract 8" when optional donut pads are installed on shaker.